



PRESSURE WASHER



BISON POWER - STRIVE



BISON MACHINERY

ABOUT US

TAIZHOU BISON MACHINERY CO., LTD.

IS ONE OF THE CHINESE LEADING MANUFACTURERS OF HIGH PRESSURE WASHER, GENERATOR, WATER PUMP, ENGINE, ETC.

BISON BRAND HAS WON ITS REPUTATION AMONG THE AREAS SOUTH AMERICA, EUROPE, AFRICA, SOUTHEAST ASIA, BY SUPPLYING QUALIFIED PRODUCTS AND PROFESSIONAL AFTER-SALE SERVICE.

WE ARE LOOKING FORWARD TO ESTABLISHING MORE WIN-WIN COOPERATION WITH CUSTOMERS ALL OVER THE WORLD.



A World-class Manufacturer of Generator,
High Pressure Washer, Engine, Water Pump



— WE ARE FAMILY, WE ARE PARTNER. —



®

BISON MACHINERY





HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION

RECOMMENDED ACCESSORIES



Rotating Car Wash Brush



1L
Foam Cannon

BS-130B


Pressure	80-100Bar 1160-1450PSI
Max Flow	9LPM/2.4GPM
Power	3.0HP/98cc
Speed	3400RPM
Start	Recoil Start
Pump Model	BSP170
Pump Head	Aluminum
Gross Weight	26kgs
Size(L×W×H)	485*385*380mm
20GP	385
40GP	900

HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Rotating Car Wash Brush



1L Foam Cannon



Surface Cleaner

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET

BS-170A

BS-180A

Pressure	150-170Bar 2200-2500PSI
Max Flow	9LPM/2.4GPM
Power	6.5HP/196cc
Speed	3400RPM
Start	Recoil Start
Pump Model	BSP170
Pump Head	Aluminum
Gross Weight	30kgs
Size(L×W×H)	550*480*530mm
20GP	192
40GP	500



Pressure	180-200Bar 2600-2900PSI
Max Flow	9LPM/2.4GPM
Power	6.5HP/196cc
Speed	3400RPM
Start	Recoil Start
Pump Model	BSP180
Pump Head	Brass
Gross Weight	31.5kgs
Size(L×W×H)	550*480*530mm
20GP	192
40GP	500

HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



1L Foam Cannon



Surface Cleaner

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET

BS-170B

Pressure	150-170Bar 2200-2500PSI
Flow	9LPM/2.4GPM
Power	6.5HP/196cc
Speed	3400RPM
Start	Recoil Start
Pump Model	BSP170
Pump Head	Aluminum
Gross Weight	30kgs
Size(L×W×H)	650*410*520mm
20GP	200
40GP	525

BS-180B




Pressure	180-200Bar 2600-2900PSI
Flow	9LPM/2.4GPM
Power	6.5HP/196cc
Speed	3400RPM
Start	Recoil Start
Pump Model	BSP180
Pump Head	Brass
Gross Weight	31.5kgs
Size(L×W×H)	650*410*520mm
20GP	200
40GP	525

HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Surface Cleaner



Water Broom

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET
6. DETERGENT TANK 2L

BS-170NA

BS-180NA

Pressure	150-170Bar 2200-2500PSI	180-200Bar 2600-2900PSI
Flow	9LPM/2.4GPM	9LPM/2.4GPM
Power	6.5HP/196cc	6.5HP/196cc
Speed	3400RPM	3400RPM
Start	Recoil Start	Recoil Start
Pump Model	BSP170	BSP180
Pump Head	Aluminum	Brass
Gross Weight	30kgs	31.5kgs
Size(L×W×H)	520*430*530mm	520*430*530mm
20GP	220	220
40GP	575	575

OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND





HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Surface Cleaner



Water Broom

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET
6. DETERGENT TANK 2L

BS-170D

BS-180D

Pressure	150-170Bar 2200-2500PSI	180-200Bar 2600-2900PSI
Flow	9LPM/2.4GPM	9LPM/2.4GPM
Power	6.5HP/196cc	6.5HP/196cc
Speed	3400RPM	3400RPM
Start	Recoil Start	Recoil Start
Pump Model	BSP170	BSP180
Pump Head	Aluminum	Brass
Gross Weight	30kgs	31.5kgs
Size(L×W×H)	595*530*580mm	595*530*580mm
20GP	168	168
40GP	344	344

OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND






HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Surface Cleaner



Gutter Cleaner

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET
6. DETERGENT TANK 2L

BS-170NC

BS-180NC

Pressure	150-170Bar 2200-2500PSI	180-200Bar 2600-2900PSI
Flow	9LPM/2.4GPM	9LPM/2.4GPM
Power	6.5HP/196cc	6.5HP/196cc
Speed	3400RPM	3400RPM
Start	Recoil Start	Recoil Start
Pump Model	BSP170	BSP180
Pump Head	Aluminum	Brass
Gross Weight	30kgs	31.5kgs
Size(L×W×H)	520*430*630mm	520*430*630mm
20GP	165	165
40GP	440	440

OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND





HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Surface Cleaner



Gutter Cleaner

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET
6. DETERGENT TANK 6L
7. HANDLE FOLDING
8. HOSE REEL

	BS-170E	BS-180E
Pressure	150-170Bar 2200-2500PSI	180-200Bar 2600-2900PSI
Flow	9LPM/2.4GPM	9LPM/2.4GPM
Power	6.5HP/196cc	6.5HP/196cc
Speed	3400RPM	3400RPM
Start	Recoil Start	Recoil Start
Pump Model	BSP170	BSP180
Pump Head	Aluminum	Brass
Gross Weight	30kgs	31.5kgs
Size(L×W×H)	840*430*580mm	840*430*580mm
20GP	140	140
40GP	280	280

OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND






HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Surface Cleaner



Sewer Jetter

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET
6. DETERGENT TANK 2L
7. HANDLE FOLDING
8. HOSE REEL

BS-170NB

BS-180NB

Pressure	150-170Bar 2200-2500PSI	180-200Bar 2600-2900PSI
Flow	9LPM/2.4GPM	9LPM/2.4GPM
Power	6.5HP/196cc	6.5HP/196cc
Speed	3400RPM	3400RPM
Start	Recoil Start	Recoil Start
Pump Model	BSP170	BSP180
Pump Head	Aluminum	Brass
Gross Weight	34kgs	36kgs
Size(LxWxH)	840*450*535mm	840*450*535mm
20GP	140	140
40GP	350	350

OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND






HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Surface Cleaner



Sewer Jetter

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. AXIAL PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET
6. DETERGENT TANK 2L
7. HANDLE FOLDING
8. HOSE REEL

BS-170CZ

BS-180CZ

Pressure	150-170Bar 2200-2500PSI	180-200Bar 2600-2900PSI
Flow	9LPM/2.4GPM	9LPM/2.4GPM
Power	6.5HP/196cc	6.5HP/196cc
Speed	3400RPM	3400RPM
Start	Recoil Start	Recoil Start
Pump Type	Vertical	Vertical
Pump Head	Aluminum	Brass
Gross Weight	34kgs	36kgs
Size(L×W×H)	565*555*620mm	565*555*620mm
20GP	120	120
40GP	336	336

OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND





HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Stainless Steel Surface Cleaner



Sewer Jetter

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. TRIPLEX PLUNGER PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET

BS-200NB

BS-250NB

Pressure	200Bar-2900PSI	250Bar-3600PSI
Flow	15LPM/4GPM	15LPM/4GPM
Power	13HP/390cc	15HP/420cc
Speed	3400RPM	3400RPM
Start	Recoil Start	Recoil Start
Pump Model	PG200	PG250
Pump Head	Brass	Brass
Gross Weight	50kgs	58kgs
Size(L×W×H)	720*580*620mm	720*580*620mm
20GP	90	90
40GP	240	240

OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND







HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND



RECOMMENDED ACCESSORIES



Turbo Nozzle



Stainless Steel Surface Cleaner

FEATURE

1. 4-STROKE OHV ,EASY START ENGINE
2. TRIPLEX PLUNGER PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET




	BS-G150A	BS-G200A	BS-G250A
Pressure	150Bar-2200PSI	200Bar-2900PSI	250Bar-3600PSI
Flow	12.6LPM/3.4GPM	15LPM/4GPM	15LPM/4GPM
Power	7HP/210cc	13HP/390cc	15HP/420cc
Speed	3400RPM	3400RPM	3400RPM
Start	Recoil Start	Recoil Start	Recoil Start/Electric Start
Pump Model	PG200	PG200	PG250
Pump Head	Brass	Brass	Brass
Gross Weight	36kgs	50kgs	58kgs
Size(L×W×H)	650*410*520mm	720*580*620mm	720*580*620mm
20GP	200	90	90
40GP	525	240	240

HIGH PRESSURE WASHER

GASOLINE



STANDARD ACCESSORIES



OPTIONAL POWER BRAND



OPTIONAL PUMP BRAND



RECOMMENDED ACCESSORIES



Turbo Nozzle



Stainless Steel Surface Cleaner

FEATURE

1. HIGH QUALITY COMPRESSION IGNITION AIR- COOLED DIESEL ENGINE
2. TRIPLEX PLUNGER PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET

	BS-G150B	BS-G200B	BS-G250B
Pressure	150Bar-2200PSI	200Bar-2900PSI	250Bar-3600PSI
Flow	12.6LPM/3.4GPM	15LPM/4GPM	15LPM/4GPM
Power	7HP/210cc	13HP/390cc	15HP/420cc
Speed	3400RPM	3400RPM	3400RPM
Start	Recoil Start	Recoil Start	Recoil Start/Electric Start
Pump Model	PG200	PG200	PG250
Pump Head	Brass	Brass	Brass
Gross Weight	42kgs	50kgs	68kgs
Size(L×W×H)	620*440*530mm	770*540*620mm	770*540*620mm
20GP	180	99	99
40GP	475	245	245







HIGH PRESSURE WASHER

DIESEL



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Stainless Steel Surface Cleaner

OPTIONAL PUMP BRAND



FEATURE

1. HIGH QUALITY COMPRESSION IGNITION AIR- COOLED DIESEL ENGINE
2. TRIPLEX PLUNGER PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET

BS-DE200A

BS-DE250A





Pressure	170Bar-2500PSI	250Bar-3600PSI
Flow	15LPM/4GPM	15LPM/4GPM
Power	6HP/296cc	10HP/418cc
Speed	3400RPM	3400RPM
Start	Recoil Start/Electric Start	Recoil Start/Electric Start
Pump Model	PG200	PG250
Pump Head	Brass	Brass
Gross Weight	64kgs	74kgs
Size(L×W×H)	760*580*620mm	760*580*620mm
20GP	90	90
40GP	240	240

HIGH PRESSURE WASHER

DIESEL



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Turbo Nozzle



Stainless Steel Surface Cleaner

OPTIONAL PUMP BRAND



FEATURE

1. HIGH QUALITY COMPRESSION IGNITION AIR- COOLED DIESEL ENGINE
2. TRIPLEX PLUNGER PUMP WITH EASY START FUNCTION
3. WATER SELF-PRIMING
4. THERMAL PROTECTION
5. ANTI-VIBRATION FEET

BS-DE200B

BS-DE250B

Pressure	170Bar-2500PSI	250Bar-3600PSI
Flow	15LPM/4GPM	15LPM/4GPM
Power	6HP/296cc	10HP/418cc
Speed	3400RPM	3400RPM
Start	Recoil Start/Electric Start	Recoil Start/Electric Start
Pump Model	PG200	PG250
Pump Head	Brass	Brass
Gross Weight	83kgs	93kgs
Size(L×W×H)	840*530*660mm	840*530*660mm
20GP	87	87
40GP	232	232







HIGH PRESSURE WASHER

ELECTRIC



STANDARD ACCESSORIES



RECOMMENDED ACCESSORIES



Rotating Car Wash Brush



1L Foam Cannon

FEATURE

1. INDUSTRIAL GRADE INDUCTION WITH GOOD START PERFORMANCE AND LOW NOISE .
2. 100% COPPER WIRE ,ALUMINUM HOUSING
3. IP55 WATER PROOF,BUILT-IN OVER-CURRENT ,LEAKAGE PROTECTION
4. TRIPLEX PLUNGER PUMP WITH PRESSURE GAUGE
5. ON-OFF SWITCH ,AUTO START AND STOP FUNCTION

SINGLE PHASE

ES1.8-2A



Working Pressure	80-100Bar/1160-1450PSI
Flow	6.5LPM/1.7GPM
Power	1.8kw
VoltageFrequency	Single phase 220V/50Hz or 220V/60Hz
Speed	2800RPM
Gross Weight	38kgs
Size(L×W×H)	600*430*470mm
20GP	240
40GP	500

HIGH PRESSURE WASHER

ELECTRIC



STANDARD ACCESSORIES



OPTIONAL PUMP BRAND



RECOMMENDED ACCESSORIES



Turbo Nozzle



1L Foam Cannon



Gutter Cleaner

FEATURE

1. INDUSTRIAL GRADE INDUCTION WITH GOOD START PERFORMANCE AND LOW NOISE .
2. 100% COPPER WIRE ,ALUMINUM HOUSING
3. IP55 WATER PROOF ,BUILT-IN OVER-CURRENT , LEAKAGE PROTECTION
4. TRIPLEX PLUNGER PUMP WITH PRESSURE GAUGE
5. ON-OFF SWITCH ,AUTO START AND STOP FUNCTION

SINGLE PHASE

	ES2.2-2	ES3-2	ES2.2-4	ES3-4
Working Pressure	100Bar/1450PSI	140Bar/2030PSI	100Bar/1450PSI	140Bar/2030PSI
Flow	12.6LPM/3.4GPM	12.6LPM/3.4GPM	12.6LPM/3.4GPM	12.6LPM/3.4GPM
Power	2.2kw	3kw	2.2kw	3kw
Voltage Frequency	Single Phase 220V/50Hz or 220V/60Hz			
Speed	2900RPM	2900RPM	1450RPM	1450RPM
Gross Weight	46kgs	48kgs	52kgs	56kgs
Size(L×W×H)	780*480*380mm			
20GP	216	216	216	216
40GP	432	432	432	432





HIGH PRESSURE WASHER

ELECTRIC



STANDARD ACCESSORIES



OPTIONAL PUMP BRAND



RECOMMENDED ACCESSORIES



Turbo Nozzle



1L Foam Cannon



Gutter Cleaner

FEATURE

1. INDUSTRIAL GRADE INDUCTION WITH GOOD START PERFORMANCE AND LOW NOISE .
2. 100% COPPER WIRE ,ALUMINUM HOUSING
3. IP55 WATER PROOF ,BUILT-IN OVER-CURRENT , LEAKAGE PROTECTION
4. TRIPLEX PLUNGER PUMP WITH PRESSURE GAUGE
5. ON-OFF SWITCH ,AUTO START AND STOP FUNCTION



THREE PHASE	ET2.2-4	ET3-4	ET4-4
Working Pressure	80-100Bar 1160-1450PSI	120-140Bar 1740-2030PSI	186-200Bar 2700-2900PSI
Flow	12.6LPM/3.4GPM	12.6LPM/3.4GPM	12.6LPM/3.4GPM
Power	2.2kw	3kw	4kw
Voltage Frequency	Three Phase 380V/50Hz or 60Hz		
Speed	1450RPM	1450RPM	1450RPM
Gross Weight	53kgs	57kgs	69kgs
Size(L×W×H)	780*480*380mm	780*480*380mm	780*480*380mm
20GP	216	216	216
40GP	432	432	432

HIGH PRESSURE WASHER

ELECTRIC



STANDARD ACCESSORIES



OPTIONAL PUMP BRAND



RECOMMENDED ACCESSORIES



Turbo Nozzle



1L Foam Cannon



Gutter Cleaner

FEATURE

1. INDUSTRIAL GRADE INDUCTION WITH GOOD START PERFORMANCE AND LOW NOISE .
2. 100% COPPER WIRE ,ALUMINUM HOUSING
3. IP55 WATER PROOF,BUILT-IN OVER-CURRENT , LEAKAGE PROTECTION
4. TRIPLEX PLUNGER PUMP WITH PRESSURE GAUGE
5. ON-OFF SWITCH ,AUTO START AND STOP FUNCTION

THREE PHASE

ET5.5-4A

ET7.5-4A




Working Pressure	250Bar/3600PSI	250Bar/2200PSI
Flow	12.6LPM/3.4GPM	15LPM/4GPM
Power	5.5kw	7.5kw
Voltage Frequency	Three Phase 380V/50Hz or 60Hz	
Speed	1450RPM	1450RPM
Gross Weight	85kgs	88kgs
Size(L×W×H)	880*490*450mm	880*490*450mm
20GP	112	224
40GP	432	432

HIGH PRESSURE WASHER

ELECTRIC



STANDARD ACCESSORIES



OPTIONAL PUMP BRAND



RECOMMENDED ACCESSORIES



Turbo Nozzle



1L Foam Cannon



Gutter Cleaner

FEATURE

1. INDUSTRIAL GRADE INDUCTION WITH GOOD START PERFORMANCE AND LOW NOISE .
2. 100% COPPER WIRE ,ALUMINUM HOUSING
3. IP55 WATER PROOF ,BUILT-IN OVER-CURRENT , LEAKAGE PROTECTION
4. TRIPLEX PLUNGER PUMP WITH PRESSURE GAUGE
5. ON-OFF SWITCH ,AUTO START AND STOP FUNCTION

THREE PHASE

ET5.5-4B

ET7.5-4B

Working Pressure	250Bar/3600PSI	250Bar/3600PSI
Flow	12.6LPM/3.4GPM	15LPM/4GPM
Power	5.5kw	7.5kw
Voltage Frequency	Three Phase 380V/50Hz or 60Hz	
Speed	1450RPM	1450RPM
Gross Weight	85kgs	88kgs
Size(L×W×H)	840*460*680mm	840*460*680mm
20GP	112	224
40GP	432	432

PRESSURE WASHER PUMP

ENGINE DRIVE

AXIAL PUMP

- 1. ENGINE DRIVE
- 2. STAINLESS STEEL PLUNGER
- 3. INTERNAL RETURN WATER PRESSURE RELIEF
- 4. THERMAL PROTECTION VALVE
- 5. SELF-PRIMING



BS-P170



BS-P180

Pump Model	Pump Head	RPM	Shaft Hole Diameter (mm)	Max Pressure (Bar)	Flow	Inlet	Outlet	G.W. (kgs)	Dimension(mm)
P170	Aluminum	3400	16/19.05	190	9LPM	1/2 QD Plug	M22×1.5	2.3	360*180*200
P180	Brass	3400	19.05	200	9LPM	1/2 QD Plug	M22×1.5	3.2	360*180*200

TRIPLEX PLUNGER PUMP

- 1. ENGINE DRIVE
- 2. ANODIZED CRANKCASE
- 3. FORGED BRASS MANIFOLD
- 4. CERAMIC COATING PLUNGER
- 5. PRESSURE ADJUSTABLE
- 6. BUILT-IN SELF SUCTION UNLOADER

OPTIONAL:

- 1. FIXED RATE CHEMICAL INJECTOR
- 2. PRESSURE GAUGE



BS-PG200



BS-PG250

Pump Model	Pump Head	RPM	Shaft Hole Diameter (mm)	Max Pressure (Bar)	Flow	Inlet	Outlet	G.W. (kgs)	Dimension(mm)
PG200	Brass	3400	19.05/25.4	220	15LPM	1/2 QD Plug	M22×1.5	7.0	390*270*250
PG250	Brass	3400	25.4	275	15/18LPM	1/2 QD Plug	3/8 QD Socket	9.0	390*270*250



PRESSURE WASHER PUMP

MOTOR DRIVE

TRIPLEX PLUNGER PUMP

1. MOTOR DRIVE
2. ANODIZED CRANKCASE
3. FORGED BRASS MANIFOLD
4. CERAMIC COATING PLUNGER
5. PRESSURE ADJUSTABLE
6. BUILT-IN SELF SUCTION UNLOADER



BS-PE180

OPTIONAL:

1. FIXED CHEMICAL INJECTOR
2. PRESSURE GAUGE
3. THERMAL RELIEF VALVE



BS-PE200



BS-PE250

Pump Model	Pump Head	RPM	Shaft Hole Diameter (mm)	Max Pressure (Bar)	Flow	Inlet	Outlet	G.W.(kgs)	Dimension(mm)
PE180	Brass	2800	24	200	12.6LPM	1/2 QD Plug	M22×1.5	5	360*180*200
PE200	Brass	1450	24/28	220	12.6LPM			7	360*180*200
PE250	Brass	1450	28	275	12.6/15LPM		3/8 QD Socket	9	360*180*200

PRESSURE WASHER ACCESSORIES:



Stainless Steel Nozzle



Sewer Jetting Nozzle



Turbo Nozzle
Max Pressure: 4000PSI/275Bar



Turbo Nozzle
Max Pressure: 3000PSI/206Bar




1L Foam Cannon



PRESSURE WASHER ACCESSORIES

HIGH PRESSURE HOSE



Model	Max. Pressure	OD mm	Inlet		Outlet	
	Bar					
BS-H01	200	11	M22×1.5		M14×1.5	
BS-H02	220	14	M22×1.5		M14×1.5	
BS-H03	320	14	3/8QD Plug	M22×1.5	3/8-QD Socket	M14×1.5
BS-H04	320	18	3/8QD Plug	M22×1.5	3/8-QD Socket	M14×1.5



Hose Reel



Inlet Hose with Suction Filter

PRESSURE WASHER ACCESSORIES

HIGH EFFICIENCY



G01

Max Pressure: 4000PSI/275BAR
Max Temperature: 60C/140F
Max Flow: 18LPM/6GPM



G02

Max Pressure: 2900PSI/200BAR
Max Temperature: 60C/140F
Max Flow: 15LPM/4GPM



Gutter Extension Wand



Bended Extension Wand



Water Broom



15" Surface Cleaner
MAX 300PSI/206Bar



Stainless Steel Surface Cleaner
MAX 4000PSI/275Bar





· 2019/2020 ·

TAIZHOU BISON MACHINERY CO., LTD

Add : Build D, No.1515 Fengnan Eastern Road, jiaoJiang,
Taizhou City, Zhejiang Province, China
Tel: 0086-576-88205202 Tel: +86-13386579061
Http:// www.bisonpower.net